

TVIPROBX2-W

2MP INDOOR DAY/NIGHT BOX HD-TVI CAMERA



FEATURES

- HD-TVI Box Camera
- 1080P (1920x1080 Resolution)
- Day & Night (ICR)
- CVBS BNC Output
- WDR Up To 120dB
- Dual Voltage
- · Lens sold separately

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA

Image Sensor 1/3" progressive scan CMOS

Signal System PAL/NTSC

Effective Pixels $1920 (H) \times 1080 (V)$

Min. Illumination Color: 0.01 Lux @ (F1.2, AGC ON)

B/W: 0.001 Lux @ (F1.2, AGC ON)

 Shutter Time
 1/25 s to 1/50,000 s

 Lens Mount
 C/CS mount

 Auto-iris
 DC drive

 Day & Night
 ICR

Synchronization Internal synchronization

WDR 120dB

HD Video Output 1 HD-TVI output

CVBS Output 1Vp-p Composite Output ($75\Omega/BNC$)

S/N Ratio More than 52dB

MENU

Scene Indoor, Outdoor, Indoor1, LOW-LIGHT

Camera ID On/off (15 characters, position programmable)

AGC Support Color/BW/EXT

White Balance ATW, AWC-SET, Indoor, Outdoor, Manual

Privacy Mask On/Off, maximum 8 zones
Motion Detection On/Off, maximum 4 zones

BLC Support Anti-flicker On/off

Language English, Japanese, CHN1, CHN2, Korean,

German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew

and Arabic

ACCESSORIES

2.8~12mm Varifocal Lens LNS21IRAI-3M



GENERAL

Working Temperature -22 °F - 140 °F

Humidity Humidity 90% or less (non-condensing)

Power Supply 24VAC,12VDC Power Consumption Max. 4.5W

Communication Up the coax (need UTC controller)

Protocol: Pelco-C (Coaxitron)

Dimensions 2.7" x 2.3" x 5.85"

Weight 1.83 lbs Warranty 3 Years



