

IPHBL4-2812M-W

4MP OUTDOOR IR WDR DAY/NIGHT
BULLET IP CAMERA



FEATURES

- 20FPS @ 4MP (2688 x 1520)
- 2.8-12mm Motorized Lens
- H.264+ / H.264 / MJPEG
- IR Range up to 100'
- WDR, DNR, Day/Night
- Outdoor IP66
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC card (128G) local storage, NAS (Support NFS, SMB, CIFS), ANR
Min. Illumination	0.01 Lux @ F1.2, AGC ON, 0.014 Lux @ F1.4, AGC ON, 0 Lux with IR	Alarm Trigger	Intrusion Detection, Line Crossing Detection, Motion Detection, Dynamic Analysis, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Shutter Speed	1/3s to 1/10,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	2.8-12mm f/1.4 motorized	General	One-key Reset, Flash-prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filtering, Anonymous Access
Lens Mount	Φ14	Standard	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
Day & Night	IR Cut Filter with Auto Switch	GENERAL	
IR Range	100'	Operating Conditions	-22 °F ~ 140 °F
DNR	3D DNR	Power Requirement	Humidity 95% or Less (Non-condensing)
WDR	120dB	Power Consumption	DC12V ± 10%, PoE (802.3af)
3-axis Angle Adjustment	Yes	Ingress Protection	Max. 5.5W, 7.5W with IR On
COMPRESSION STANDARD		Dimensions	IP66
Video Compression	H.264+ / H.264 / MJPEG	Weight	3.74" x 4.13" x 10.19"
Type	Main Profile H.264	Warranty	2.65 lbs
Video Bit Rate	32 Kbps ~ 16 Mbps	Package Contents	3 Years
Dual streams	Support		Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Audio	G.711 / G.726 / MP2L2 64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-128Kbps (MP2L2)		
IMAGE			
Max. Resolution	2688 x 1520		
Frame Rate	50Hz: 20FPS @ 2688 x 520, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 20FPS @ 2688 x 1520, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast Adjustable by Client Software or Web Browser		
BLC	Support		
ROI Codec	Support		
ACCESSORIES			
Junction Box JB200	Pole Mount POLEMT5		
			

