

# IPHEBX4-3-W

## 4MP OUTDOOR IR DAY/NIGHT EYEBALL IP CAMERA




### FEATURES

- 20FPS @ 4MP (2688 x 1520)
- 2.8mm Fixed Lens
- H.264+ / H.264 / MJPEG
- IR Range up to 100'
- WDR, DNR, Day/Night
- Outdoor IP66, Vandal-proof
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

### SPECIFICATIONS

<b>CAMERA</b>		<b>NETWORK</b>	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	NAS (Support NFS,SMB/CIFS), ANR
Min. Illumination	0.01Lux @ F1.2, AGC ON, 0 Lux with IR	Alarm Trigger	Intrusion Detection, Line Crossing Detection, Motion Detection, Dynamic Analysis, Tampering alarm, Network Disconnect, IP Address Conflict, Storage Exception
Shutter Speed	1/3s to 1/10,000s	Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens / Angle of View	2.8mm / 106°	General	Flash-prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filtering, Anonymous Access
Lens Mount	M12	Standard Interface	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
Day & Night	IR cut filter with auto switch	GENERAL	
IR Range	100'	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
DNR	3D DNR	Power Requirement	DC12V ± 10%, PoE (802.3af)
WDR	120dB	Power Consumption	Max. 5.5W (Max. 7.5W with IR on)
3-axis Angle Adjustment	Pan: 0°~360°, Tilt: 0°~75°, Rotation: 0°~360°	Ingress Protection	IP66
<b>COMPRESSION STANDARD</b>		Dimensions	5.0" x 3.8"
Video Compression	H.264+ / H.264 / MJPEG	Weight	1.5 lbs
Type	Main Profile H.264	Warranty	3 Years
Video Bit Rate	32 Kbps ~ 16 Mbps	Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Dual streams	Support		
<b>IMAGE</b>			
Max. Resolution	2688 x 1520		
Frame Rate	50Hz: 20FPS @ 2688 x 1520, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 20FPS @ 2688 x 1520, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support, Zone configurable		
ROI Codec	Support		
<b>ACCESSORIES</b>			
Junction Box JB210	Wall Mount WM315	Pole Mount POLEMT5	



Unit: mm