

TVIPROID2-21M-B

1080p INDOOR IR DAY/NIGHT DOME HD-TVI/ANALOG CAMERA W/ 2.8-12MM MOTORIZED LENS



FEATURES

- HD 1080p Video Output
- Adopt HD-TVI Technology
- True Day/Night
- 2.8-12mm Motorized Lens
- · OSD menu, 3D DNR, Smart IR
- Up to 100 ft IR distance
- Up the Coax (via coaxial cable)
- True WDR, 120 dB

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards. Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA 1/3" Progressive Scan CMOS **Image Device** Signal System PAL/NTSC **Effective Pixels** 1920 (H) x 1080 (V)

Min. Illumination 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR,

0.014 Lux @ (F1.4,AGC ON),0 Lux with IR

Shutter Time 1/25(1/30)s to 1/50,000s 2.8-12mm Motorized @ F1.4 Lens

Angle of view 103° - 32.1°

Lens Mount

Pan: 0 - 355°, Tilt: 0 - 180°, Rotation: 0 - 355° Angle Adjustment **ICR**

Day & Night

Synchronization Internal synchronization

WDR 120dB

25FPS @ 1080p PAL / 30FPS @ 1080p NTC Video Frame Rate

HD Video Output 1 1080p TVI output

CVBS Output 1Vp-p Composite Output(75Ω/BNC)

S/N Ratio More than 52dB

MENU Indoor, Outdoor, Indoor1, LOW-LIGHT Scene

Camera ID On/off (15 characters, position programmable)

AGC Support D/N Mode Color / BW / EXT

White Balance ATW, AWC-SET, Indoor, Outdoor, Manual

Privacy Mask On/Off, maximum 8 zones

Motion Detection On/Off, maximum 4 zones

BLC Support Anti-flicker On / Off

Language English, Japanese, CHN1, CHN2, Korean,

> German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew

Eclipse, Digital noise reduction, Digital zoom **Functions**

(62x), Slow shutter, Mirror, Defog, Defect pixel

correction, SMART D-ZOOM

GENERAL

Working Temperature 1-4 °F - 113 °F

Humidity Humidity 90% or less (non-condensing)

Power Supply 12 VDC, 24 VAC

Power Consumption 12 VDC: Max. 4.5W; 24 VAC: Max. 6.5W


IR Range Up to 100 ft

Communication Up the coax(need UTC controller),

Protocol: Pelco-C(Coaxitron)

Dimensions Φ 5.35" × 3.98" 3 Years Warranty Weight 0.84 lb





Unit: mm