

TVIPROID2-21-W

1080p INDOOR IR DAY/NIGHT DOME HD-TVI/ANALOG CAMERA W/ 2.8-12MM VARIFOCAL LENS



FEATURES

- HD 1080p Video Output
- Adopt HD-TVI Technology
- True Day/Night
- 2.8–12mm Vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 100 ft IR distance
- Up the Coax (via coaxial cable)
- True WDR, 120 dB

Shutter Time

MENU

Language

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA
Image Device 1/3" Progressive Scan CMOS
Signal System PAL/NTSC
Effective Pixels 1920 (H) x 1080 (V)

Min. Illumination 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR,

0.014 Lux @ (F1.4,AGC ON),0 Lux with IR

1/25(1/30)s to 1/50,000s

Lens True Day/Night with ICR motorized filter control

Angle of view 103° - 32.1°

Angle Adjustment Pan: 0 - 355°, Tilt: 0 - 180°, Rotation: 0 - 355°

Day & Night ICR

Synchronization Internal synchronization

WDR 120dB

Video Frame Rate 25FPS @ 1080p PAL / 30FPS @ 1080p NTC

HD Video Output 1 1080p TVI output

CVBS Output 1Vp-p Composite Output(75Ω/BNC)

S/N Ratio More than 52dB

Scene Indoor, Outdoor, Indoor1, LOW-LIGHT

Camera ID On/off (15 characters, position programmable)

 AGC
 Support

 D/N Mode
 Color / BW / EXT

White Balance ATW, AWC-SET, Indoor, Outdoor, Manual

Privacy Mask On/Off, maximum 8 zones

Motion Detection On/Off, maximum 4 zones

BLC Support
Anti-flicker On / Off

English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish,

Russian, Portuguese, Dutch, Turkish, Hebrew

and Arabic

Functions Eclipse, Digital noise reduction, Digital zoom

(62x), Slow shutter, Mirror, Defog, Defect pixel

correction, SMART D-ZOOM

GENERAL

Working Temperature 1-4 °F – 113 °F

Humidity Humidity 90% or less (non-condensing)

Power Supply 12 VDC, 24 VAC

Power Consumption 12 VDC: Max. 4.5W; 24 VAC: Max. 6.5W

IR Range Up to 100 ft

Communication Up the coax(need UTC controller),

Protocol: Pelco-C(Coaxitron)

Unit: mm

Dimensions Φ 5.35" × 3. 98"

Weight 0.84 lb



