



IPHPHL2-4

2MP INDOOR WDR DAY/NIGHT
PINHOLE COVERT IP CAMERA



FEATURES

- 30FPS @ 2MP (1920 x 1080)
- 3.7mm Lens
- H.264 / MJPEG
- WDR, DNR, Day/Night, Defog
- Indoor
- 12VDC, PoE
- Available in Black

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.7" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC Card (128GB) Local Storage; Edge Recording, NAS, NFS, SMB, CIFS
Min. Illumination	0.01 Lux @ f/1.2 AGC On	Alarm Trigger	Motion Detection, Face Detection, Dynamic Analysis, Tampering Alarm, Network Disconnect, IP Address Conflicts, Storage Full, Storage Error, Intrusion Detection, Line Crossing Detection, Defocus, Detection, Audio Exception Detection, Scene Change Detection
Shutter Speed	1s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	3.7mm	General	Reset, Flickerless, Multi-stream, Heartbeat, Rotate, Password Protection, Video Masking, Watermark, Anonymous Login, IP Address Filtering
Lens Mount	M12	Standard Interface	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
Lens Cable	6'	Audio Interface	1 RJ45 10M / 100M Ethernet Interface
Angle of View	65°	Alarm Input	1 3.5mm Audio In Mic In / Line In / Out
Day & Night	Auto / Timing / Alarm Trigger	Alarm Output	1 Channel
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or Less Non-condensing
COMPRESSION STANDARD		Power Requirement	12 VDC ± 10% , PoE (802.3af)
Video Compression	H.264 / MJPEG	Power Consumption	Max. 6.5W
Type	Main Profile H.264	Dimensions	3.07" x 4.13" x 1.26"
Video Bitrate	32 Kbps ~ 16 Mbps	Weight	1.50 lbs
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2	Warranty	3 Years
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-160Kbps (MP2L2)	Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories, 6' Cable
Triple Streams	Support		
IMAGE			
Max. Resolution	1920 x 1080		
Frame Rate	50Hz: 25FPS @ 1920 x 1080, 25FPS @ 1280 x 960, 25FPS @ 1280 x 720 60Hz: 30FPS @ 1920 x 1080, 30FPS @ 1280 x 960, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode (First Channel), Saturation, Brightness, Contrast, Sharpness and Gray Scale Adjustable		
BLC	Yes, Zone Optional		
ROI	Up to 4 Fixed Areas in Each Stream		



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900