

IPHLPD4-3-W

4MP OUTDOOR IR DAY/NIGHT
LOW PROFILE DOME IP CAMERA



FEATURES

- 20FPS @ 4MP (2688 x 1520)
- 2.8mm Fixed Lens
- H.264+ / H.264 / MJPEG
- IR Range up to 30'
- WDR, DNR, Day/Night
- Outdoor IP66, Vandal-proof IK08
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC card (128GB) local, NAS (Supports NFS, SMB, / CIFS), ANR
Min. Illumination	0.01 Lux @ F1.2, AGC ON, 0 Lux with IR	Alarm Trigger	Motion Detection, Tampering Alarm
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMPP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGM, 802.1X, QoS, IPv6, Bonjour
Lens	2.8mm f/2.0	General	One-key Reset, Flash-prevention, Watermark, Dual Stream, Heartbeat, Mirror, Privacy Mask, Password Protection, IP Address Filtering, Anonymous Access
Lens Mount	M12	Standard Interface	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
Day & Night	IR Cut Filter with Auto Switch	Alarm Interface	1 RJ45 10M / 100M Ethernet Interface
IR Range	30'	Audio Interface	1 x Alarm I/O
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
3-axis Angle Adjustment	Pan: -30°~30°, Tilt: 0°~75°, Rotation: 0°~360°	Power Requirement	DC12V ± 10%, PoE (802.3af)
COMPRESSION STANDARD		Power Consumption	Max. 5
Video Compression	H.264+ / H.264 / MJPEG	Ingress Protection	IP66
Type	Main Profile H.264	Impact Protection	IEC60068-275Eh, 20J; EN50102, up to IK08
Video Bit Rate	32 Kbps ~ 16 Mbps	Dimensions	3.91" x 3.81" x 2.08"
Dual Streams	Support	Weight	1.32 lbs
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2	Warranty	3 Years
Audio Bit Rate	64 Kbps (G.711) / 16 Kbps (G.722.1) / 16 Kbps (G.726) / 32-128 Kbps (MP2L2)	Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories, Mounting Plate, Mounting Screws, Weathertight Connector
IMAGE			
Max. Resolution	2688 x 1536		
Frame Rate	50Hz: 20FPS @ 2688 x 1520, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 20FPS @ 2688 x 1520, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support, Zone Configurable		
ROI Codec	Support		
			