

IPHVD8-3-W

8MP OUTDOOR IR DAY/NIGHT
RUGGED DOME IP CAMERA



FEATURES

- 15FPS @ 8MP (3480 x 2160)
- 2.8mm Fixed Lens
- H.265 / H.264
- IR Range up to 100'
- WDR, DNR, Day/Night
- Outdoor IP67, Vandal-proof IK10
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA Image Sensor 1/2.5" Progressive Scan CMOS Min. Illumination 0.01 Lux @ F1.2, AGC ON, 0 Lux with IR Shutter Speed 1/3s to 1/100,000s Lens 2.8mm Lens Mount M12 Day & Night IR Cut Filter with Auto Switch IR Range 30' DNR 3D DNR WDR 120dB 3-axis Angle Adjustment Pan: 0°~355°, Tilt: 0°~75°, Rotation: 0°~355°		NETWORK Network Storage micro SD/SDHC/SDXC card (128GB) local storage, NAS (NFS, SMB, / CIFS), ANR Alarm Trigger Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Illegal Login, HDD Full, HDD Error Protocols TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 General One-key Reset, Anti-Flicker, Watermark, Heartbeat, Mirror, Privacy Mask, Password Protection, IP Address Filtering, ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI Standard Interface 1 RJ45 10M / 100M Self-adaptive Ethernet Interface	
COMPRESSION STANDARD Video Compression H.265 / H.264 Type Main Profile H.265 / H.264 Video Bit Rate 32 Kbps ~ 16 Mbps Triple Streams Support		GENERAL Operating Conditions -22 °F ~ 140 °F, Humidity 95% or less (non-condensing) Power Requirement DC12V ± 10%, PoE (802.3af, class 3) Ingress Protection IP67 Impact Protection IK10 Dimensions Φ4.4" x 3.2" Weight 1.1 lbs Warranty 3 Years Package Contents Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector	
IMAGE Max. Resolution 3840 x 2160 Frame Rate 50Hz: 15FPS @ 3840 x 2160, 25FPS @ 2560 x 1920, 25FPS @ 2540 x 1440, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 15FPS @ 3840 x 2160, 30FPS @ 2560 x 1920, 30FPS @ 2560 x 1440, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720 Image Setting Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser BLC Support ROI Codec Support			
ACCESSORIES Junction Box JB250 Wall Mount WM210 Wall Mount WM215 Wall Mount WM215BB with Back Box Pole Mount POLEMT5			