



IPHPTZ3-36X-ATIR

3MP OUTDOOR IR WDR DAY/NIGHT
RUGGED PTZ IP CAMERA



FEATURES

- 30FPS @ 3MP (2048 x 1536)
- 4.6-162mm 36x Optical Zoom Lens
- H.264 / MJPEG
- IR Range up to 650'
- WDR, DNR, Day/Night, Smart Auto Tracking, Defog
- Outdoor IP66, Vandal-proof IK10
- 24VAC, High-PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	Up to 8 NAS Storage; Edge Recording (Transmits Video From SD Card to NAS After Network Resumes)
Min. Illumination	Color: 0.05 Lux @ f/1.6, AGC ON, B/W: 0.01 Lux	Alarm Trigger	Face Detection, Intrusion Detection, Line Crossing Detection, Region Entrance, Region Exiting, Audio Exception Detection, Motion Detection, Dynamic Analysis, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Shutter Speed	1s to 1/30,000s	Protocols	IPv4 / IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Lens	4.6-162mm 36x Optical Zoom	Standard Interface	ONVIF, PSIA, CGI, Genetec
Angle of View	60.6° to 3.68° (Wide to Tele)	Audio Input	10Base-T / 100Base-TX, RJ-45 Connector
Day & Night	IR Cut Filter	Audio Output	1 Mic in / Line in Interface, Line Input: 2 to 2.4 V [p-p]; Output Impedance: 1K Ω , $\pm 10\%$
IR Range	650'		1 Audio Output Interface, Line Level, Impedance: 600 Ω
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-40 °F ~ 149 °F, Humidity 90% or less (non-condensing)
Pan and Tilt	Pan: 360° Endless, Tilt: -20°~90° (auto flip)	Power Requirement	24VAC High PoE
Speed	Pan Manual Speed: 0.1° to 160°/s, Pan Preset Speed: 240°/s	Power Consumption	Max. 60W
Number of Presets	300	Ingress Protection	IP66, IK10, TVS 6,000 V Lightning Protection, Surge Protection and Voltage Transient Protection
Patrols	16 Patrols, Up to 32 Presets Per Patrol	Dimensions	10.5" x 14.38"
Smart Auto Tracking	Manual, Panorama, Intrusion Trigger, Line, Crossing Trigger, Region Entrance Trigger, Region Exiting Trigger, Smart Tracking When Patrol Between Multiple Scenarios	Weight	17.64 lbs
COMPRESSION STANDARD		Warranty	1 Year
Video Compression	H.264 / MJPEG	Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Type	Main Profile H.264	ACCESSORIES	
Triple streams	Support	Wall Mount Bracket WM610	
Audio Compression	G.711ulaw / G.711alaw / G.726 / MP2L2 / G.722		
IMAGE			
Max. Resolution	2048 x 1536		
Frame Rate	60Hz: 30FPS @ 2048 x 1536, 60FPS @ 1920 x 1080, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support		
ROI Codec	Support		



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900