



TVIPROLB5-21M-W

5MP OUTDOOR IR DAY/NIGHT
BULLET HD-TVI CAMERA






FEATURES

- 5MP (2592 x 1944) Resolution
- 2.8~12mm Motorized Lens
- HD-TVI Output
- IR Range Up to 130'
- DNR, Day/Night
- Outdoor IP67
- 12VDC/24VAC
- Available in White

Rainvision is a leading brand of IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		GENERAL	
Imaging Sensor	1/2.8" Progressive Scan CMOS	Operating Conditions	-40 °F ~ 140 °F, Humidity: 90% or Less Non-condensation
Min. Illumination	Color: 0.01 Lux @ F1.2, AGC ON, 0 Lux with IR	Power Requirement	12 VDC, 24 VAC
Shutter Speed	PAL: 1/25s to 1/50,000s, NTSC: 1/30s to 1/50,000s	Power Consumption	Max. 9W
Lens	2.8-12mm Motorized Lens	Ingress Protection	IP67
Lens Mount	Φ14	Dimensions	3.62" x 3.34" x 3.34"
Horizontal Field of View	86.8° to 27.7°	Weight	1.98 lbs
Day & Night	IR Cut Filter	Package Contents	Camera, Installation Manual/Template, Installation Accessories
IR Range	130'		
DNR	DNR		
3-axis Angle Adjustment	Pan: 0° - 360°, Tilt: 0° - 90°, Rotate: 0° - 360°		
Synchronization	Internal Synchronization		
Communication	Up to Coax, HD-TVI Output		
IMAGE			
Max. Resolution	2592 x 1944		
Frame Rate	20FPS @ 5MP (2592 x 1944)		
Image Setting	Brightness, Sharpness, Digital Noise Reduction, Mirror, Bad Pixel Correction, Smart IR		
BLC	Support		
AGC	Support		
D/N Mode	Auto / Color / Black and White		
White Balance	ATW / MWB		
ACCESSORIES			
Junction Box JB150		Pole Mount POLEMT5	
			



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900