

TVIPROVD2-3-W

1080p OUTDOOR IR DAY/NIGHT DOME HD-TVI CAMERA W/ 2.8MM LENS



FEATURES

- 2MP Resolution
- 2.8mm Lens
- HD-TVI Output
- EXIR Range up to 65'
- OSD menu, 3D DNR, Smart IR
- · Outdoor IP67, Vandal-proof IK7
- 12VDC
- · Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards. Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA Image Device 1/3" Progressive Scan CMOS

Signal System PAL/NTSC **Effective Pixels** 1920 (H) x 1080 (V)

Min. Illumination Color: 0.005 Lux @ (F2.0, AGC ON),

0 Lux with IR

Shutter Time PAL: 1/25 s to 1/50,000s

NTSC: 1/30s to 1/50,000s

Lens 2.8mm Horizontal Field of View 103.5° Lens Mount M12

Angle Adjustment Pan: 0° to 360°, Tilt:0° to 75°, Rotate: 0° to 360°

Day & Night IR Cut Filter

Synchronization Internal Synchronization

WDR > 120 dB

Video Frame Rate PAL: 25FPS @ 1080p / NTSC: 30FPS @ 1080p

HD Video Output 1 1080p TVI Output

MENU

AGC Support D/N Mode Auto / Color / BW White Balance ATW / Manual

ON/OFF, 4 Programmable Privacy Masks **Privacy Mask**

Motion Detection 4 Programmable Motion Areas **BLC** WDR / BLC / HLC / OFF

3D DNR On

Language English, Chinese

Brightness, Sharpness, Mirror, Smart IR **Functions**

ACCESSORIES

Junction Box JB250



Pole Mount POLEMT5



Wall Mount WM210



Wall Mount WM215BB with Back Box

GENERAL

Working Temperature -40 °F - 140 °F

Humidity Humidity 90% or Less (Non-condensing)

Power Supply 12 VDC ± 25% **Power Consumption** Max. 3.5 W IR Range Up to 65 ft Communication Up the Coax Dimensions Φ 4.4" × 3.2" Warranty 3 Years Weight

Package Contents Camera, Installation Manual/Template,

Installation Accessories



