

TVIPROVD2-21M3-W

1080p OUTDOOR IR DAY/NIGHT DOME HD-TVI CAMERA W/ 2.8-12MM MOTORIZED LENS



FEATURES

- 2MP Resolution
- 2.8–12mm Motorized Vari-focal Lens
- HD-TVI Output
- EXIR Range up to 130' IR
- OSD menu, 3D DNR, Smart IR
- · Outdoor IP67, Vandal-Proof IK8
- 12VDC/24VAC

Lens

· Available in White

Rainvision is a leading brand of IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards. Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA 1/3" Progressive Scan CMOS **Image Device** Signal System PAL/NTSC

Effective Pixels 1920 (H) x 1080 (V) Min. Illumination

Color: 0.005 Lux @ (F1.8, AGC ON),

0 Lux with IR

Shutter Time PAL: 1/25 s to 1/50,000s NTSC: 1/30s to 1/50,000s

2.8~12mm Motorized Vari-focal Lens

Horizontal Field of View 32.1° - 103.5°

Lens Mount Ф14

Angle Adjustment Pan: 0° to 340°, Tilt: 0° to 75°, Rotate: 0° to 355°

Day & Night IR Cut Filter IR Range Up to 130'

Internal Synchronization Synchronization

WDR > 120 dB

NTSC: 30FPS @ 1080p / PAL: 25FPS @ 1080p Video Frame Rate

ATW / Manual

1 1080p TVI Output **HD Video Output**

MENU Support **AGC** D/N Mode Auto / Color / BW

Privacy Mask ON/OFF, 4 Programmable Privacy Masks

Motion Detection 4 Programmable Motion Areas WDR / BLC / HLC / OFF

3D DNR On

Language English, Chinese

Functions Brightness, Sharpness, Mirror, Smart IR

ACCESSORIES

White Balance

BLC

Wall Mount WM320 Wall Mount WM320BB

GENERAL

Working Temperature -40 °F - 140 °F

Humidity Humidity 90% or Less (Non-condensing)

Power Requirement 12VDC / 24VAC **Power Consumption** Max. 7 W

Communication Up the Coax, TVI Output Φ 5.72" x 4.89"

Dimensions Warranty 3 Years Weight 3.53 lbs

Package Contents Camera, Installation Manual/Template,

Installation Accessories

