



IPHLPR2-83M-W

2MP OUTDOOR IR WDR DAY/NIGHT
LPR IP CAMERA



FEATURES

- 60FPS @ 2MP (1920 x 1080)
- 8-32mm Motorized Lens
- LPR Capture Distance (2 Car Lanes): 35 ft ~ 100 ft
- H.264 / MPEG4 / MJPEG
- IR Range up to 330'
- WDR, DNR, Day/Night
- Outdoor IP67
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.8" Progressive Scan CMOS	Network Storage	Micro SD/SDHC/SDXC card (128GB), Local Storage and NAS (NFS, SMB/CIFS), ANR
Min. Illumination	0.002 Lux @ F1.2, AGC ON, 0.0027 @ F1.4 AGC On, 0 Lux with IR	Alarm Trigger	Road Traffic, Motion Detection, Video Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error
Shutter Speed	1s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	8 to 32mm Motorized	General	One-key Reset, Dual-VCA, Anti-flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Day & Night	IR Cut Filter with Auto Switch	API	ONVIF (Profile S, Profile G), ISAPI
IR Range	330'	Interface	1 RJ45 10M/100M Self Adaptive Ethernet Port
DNR	3D DNR	Audio Interface	1 Input, 1 Output
WDR	120dB	GENERAL	
COMPRESSION STANDARD		Operating Conditions	-22° F ~ 140° F, Humidity 95% or Less (Non-condensing)
Video Compression	H.264 / MPEG4	Power Requirement	DC12V ± 10%, Terminal Block PoE (802.3at, class 4)
Type	Main Profile H.264	Power Consumption	Max 17.6 W
Video Bit Rate	32 Kbps ~ 16 Mbps	Ingress Protection	IP67, Lightning Protection, Surge Protection, Voltage Transient, Anti-static Protection
Triple Streams	Supported	Dimensions	3.94" x 4.09" x 12.28"
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2	Weight	4.57 lbs
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-192Kbps (MP2L2)	Warranty	3 Years
IMAGE		Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Junction Box
Max. Resolution	1920 x 1080		
Main Stream	50Hz: 50fps (1920 x 1080, 1280 x 960, 1280 x 720) 60Hz: 60fps (1920 x 1080, 1280 x 960, 1280 x 720)		
Third Stream	Supported		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support		
ROI	Four Fixed Regions for Each Stream and Dynamic Tracking		
LICENSE PLATE RECOGNITION			
LPR Capture Distance (2 Car Lanes)	35 ft ~ 100 ft		
Accuracy	Capture Rate Up to 99% Recognition Rate Up to 95%		
Vehicle Speed	Captures Speeds Up to 75MPH		
Direction	Supports Capture and Recognition of Vehicles Entering and Leaving		
Whitelist / Blacklist	Up to 2,048		



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900