

IPH2LPD4-3-W

4MP OUTDOOR IR DAY/NIGHT
LOW PROFILE DOME IP CAMERA



FEATURES

- 20FPS @ 4MP (2688 x 1520)
- 2.8mm Fixed Lens
- H.265 / H.264
- IR Range up to 30'
- WDR, DNR, Day/Night
- Outdoor IP66, Vandal-proof IK08
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	MicroSD/SDHC/SDXC card (128G), Local Storage and NAS (NFS,SMB/CIFS), ANR
Min. Illumination	0.01 lux @ F1.2, AGC ON, 0 lux with IR	Alarm Trigger	Motion Detection, Video Tampering, Network Disconnected, IP Address Conflict, HDD Full, HDD Error, Illegal Login
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6
Lens	2.8mm f/1.6	General	One-key Reset, Anti-flicker, Three Streams, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Day & Night	IR Cut Filter with Auto Switch	Standard Interface	ONVIF (PROFILE S, PROFILE G), ISAPI
IR Range	30'	Alarm Interface	1 RJ45 10M/100M Self-adaptive Ethernet Port
DNR	3D DNR	Audio Interface	1 Input: Alarm in (3.5mm), 1 Output: Alarm out (3.5mm)
WDR	120dB		2 Inputs: Line In (3.5 mm) or Mic In (Built-in Microphone), 1 Output: Line Out (3.5 mm), Mono Sound
3-axis Angle Adjustment	Pan: -30°~30°, Tilt: 0°~75°, Rotation: 0°~360°	GENERAL	
Field of View	Horizontal: 98°, Vertical: 55°, Diagonal: 114°	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
COMPRESSION STANDARD		Power Requirement	DC12V ± 25%, PoE (802.3af, Class 3)
Video Compression	H.265 / H.264	Power Consumption	12 VDC, 0.7A, Max. 8.5 W, PoE (802.3af, 36V-57V), 0.3-0.1 Amp, Max. 10 W
H.264 Type	Main Profile / High Profile	Ingress Protection	IP66
H.265 Type	Main Profile	Impact Protection	IK08
Video Bit Rate	32 Kbps ~ 16 Mbps	Dimensions	Φ 4.3" x 2.2"
three Streams	Supported	Weight	.9 lbs
Audio Compression	G722.1 / G711ulaw / G711alaw / G726 / MP2L2 / PCM	Warranty	3 Years
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-192Kbps (MP2L2)	Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories, Mounting Plate, Mounting Screws, Weathertight Connector
IMAGE			
Max. Resolution	2688 x 1536		
Frame Rate	50Hz: 25fps (2688 x 1520, 2304 x 1296, 1920 x 1080), 60Hz: 30fps (2688 x 1520, 2304 x 1296, 1920 x 1080)		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Supported		