



IPH2EBX4-3-W

4MP OUTDOOR IR DAY/NIGHT
EYEBALL IP CAMERA



FEATURES

- 30FPS @ 4MP (2688 x 1520)
- 2.8mm Fixed Lens
- H.265+ / H.265 / H.264+ / H.264
- IR Range up to 100'
- WDR, DNR, Day/Night
- Outdoor IP66
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	Support Micro SD/SDHC/SDXC Card (128G), Local Storage and NAS(NFS,SMB/CIFS), ANR
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR	Alarm Trigger	Motion detection, Video Tampering, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens / Angle of View	2.8mm / 103° Horizontal, 58° Vertical, 123° Diagonal	General	One-key Reset, Anti-flicker, Three Streams, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Day & Night	IR Cut Filter	Standard Interface	ONVIF (PROFILE S, PROFILE G), ISAPI
IR Range	100'		1 RJ45 10M / 100M Self-adaptive Ethernet Interface
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
3-axis Angle Adjustment	Pan: 0°~360°, Tilt: 0°~75°, Rotation: 0°~360°	Power Requirement	DC12V ± 15%, PoE (802.3af, Class 3)
COMPRESSION STANDARD		Power Consumption	12 VDC, 0.5A, Max. 6W, PoE (802.3af, 37V to 57V), 0.2A to 0.1A, max. 7.5W
Video Compression	H.264+ / H.264 / MJPEG	Ingress Protection	IP67, TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
Type	Main Profile H.265 / H.264	Dimensions	5.0" x 3.8"
Video Bit Rate	256 Kbps to 16 Mbps	Weight	1.3 lbs
Three Streams	Support	Warranty	3 Years
IMAGE		Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Max. Resolution	2688 x 1520		
Frame Rate	50Hz:25fps (2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080), 60Hz: 30fps (2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080)		
Image Setting	Rotate mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support		
ROI Codec	Support		
ACCESSORIES			
Junction Box JB210	Wall Mount WM315	Pole Mount POLEMT5	
			
			
			
			Unit: mm



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900