

TVIHD5EB-3-W

5MP OUTDOOR IR DWDR DAY/NIGHT EYEBALL HD-TVI CAMERA



FEATURES

- 5MP (2560 x 1944) Resolution
- 2.8mm Fixed Lens
- HD-TVI / HD-CVI / AHD / Analog Video Ouput
- IR Range up to 65'
- DWDR, DNR, Day/Night
- Outdoor IP67
- 12VDC
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA **Image Sensor** 5MP CMOS Image Sensor Min. Illumination Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR **Shutter Speed** PAL: 1/25s to 1/50,000s NTSC: 1/30s to 1/50,000s Lens 2.8mm Fixed Lens Day & Night IR Cut Filter IR Range 130' 2D DNR **DWDR** Supported 3-axis Adjustment

Pan: 0°~360°, Tilt: 0°~75°, Rotate: 0°~360°

Horizontal Field of View 85.5°

Synchronization Internal Synchronization Communication Up the Coax, HD-TVI Output

IMAGE

Max. Resolution 2560 x 1944

Frame Rate PAL: 20FPS@ 5MP, 25FPS @ 4MP,

25FPS @ 1080p, NTSC: 20FPS @ 5MP,

30FPS @ 4MP, 30FPS @ 1080p

Image Settings Brightness, Sharpness, DNR, Mirror, Smart IR

BLC Support **AGC** Support

D/N Mode Auto / Color / Black and White

White Balance ATW / MWB **GENERAL**

Operating Conditions -40 °F ~ 140 °F

Power Requirement 12VDC ± 25%

Power Consumption Max. 4.3W **Ingress Protection** IP67

Dimensions 3.58" x 3.25" x 2.69"

Weight .77 lbs Warranty 3 Years

Package Contents Camera, Installation Manual/Template,

Installation Accessories

Humidity 90% or Less (Non-condensing)

