

TVIHD5VD-21M-W

5MP OUTDOOR IR DAY/NIGHT DOME HD-TVI CAMERA W/ 2.8-13.5MM MOTORIZED LENS



FEATURES

- 5MP (2592 x 1944) Resolution
- 2.8~13.5mm Motorized Lens
- HD-TVI / HD-CVI / AHD Video Output
- IR Range Up to 130'
- DWDR, DNR, Day/Night
- Outdoor IP67, Vandal-proof IK10
- 12VDC/24VAC
- · Available in White or Black

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA **Image Sensor** 5MP CMOS Image Sensor

Min. Illumination Color: 0.01 Lux @ (F1.2, AGC ON),

0 Lux with IR

PAL: 1/25s to 1/50,000s **Shutter Speed**

NTSC: 1/30s to 1/50,000s

Lens 2.7~13.5mm Motorized Varifocal Lens

Day & Night IR Cut Filter IR Range Up to 130' 2D DNR **DWDR** Supported

3-axis Adjustment Pan: 0°~355°, Tilt: 0°~75°, Rotate: 0°~355°

Horizontal Field of View 95.7°~29.1°

Synchronization Internal Synchronization Communication Up the Coax, HD-TVI Output

IMAGE

Max. Resolution 2560 x 1944

Frame Rate PAL: 20FPS@ 5MP, 25FPS @ 4MP,

> 25FPS @ 1080p, NTSC: 20FPS @ 5MP, 30FPS @ 4MP, 30FPS @ 1080p

Image Settings Brightness, Sharpness, DNR, Mirror, Smart IR

BLC Support **AGC** Support

D/N Mode Auto / Color / Black and White

White Balance ATW / MWB **GENERAL**

Operating Conditions -40 °F ~ 140 °F

Humidity 90% or Less (Non-condensing) **Power Requirement** 12 VDC ±15%, 24 VAC ±15%


Max. 6W **Power Consumption**

Ingress Protection IP67, IK10 **Dimensions** Ø 5.5" x 5.0" Weight 1.44 lbs Warranty 3 Years

Package Contents Camera, Installation Manual/Template,

Installation Accessories





Camera base has multiple screw holes so the camera can be mounted to standard size electrical boxes.