

## TVIHD8ID-21M-W

8MP INDOOR IR DAY/NIGHT DOME HD-TVI CAMERA



## **FEATURES**

- 15FPS @ 8MP (3840 x 2160)
- 2.7~13.5mm Motorized Auto-focus Lens
- HD-TVI / HD-CVI / AHD / Analog Video Ouput
- IR Range up to 200'
- DWDR, DNR, Day/Night
- Indoor
- 12VDC / 24VDC
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

## **SPECIFICATIONS**

CAMERAImage Sensor8.29 MP CMOS Image SensorMin. IlluminationColor: 0.01 Lux @ (F1.2, AGC ON),

0 Lux with IR

Shutter Speed PAL: 1/12.5s to 1/50,000s NTSC: 1/15s to 1/50,000s

2.7~13.5mm Motorized Auto-focus Lens

 Day & Night
 IR Cut Filter

 IR Range
 200'

 DNR
 Supported

 DWDR
 105 dB

**3-axis Adjustment** Pan: 0°~340°, Tilt: 0°~75°, Rotate: 0°~355°

Horizontal Field of View 108.1°~45.6°

Synchronization Internal Synchronization
Communication Up the Coax, HD-TVI Output

**IMAGE** 

Lens

Max. Resolution 3840 x 2160

Frame Rate HD-TVI: 15FPS @ 8MP, 12.5FPS @ 8MP,

20FPS @ 5MP, 30FPS @ 4MP, 25FPS @ 4MP,

30FPS @ 2MP, 25FPS @ 2MP, HD-CVI: 15FPS @ 8MP, 12.5FPS @ 8MP AHD: 20FPS @ 5MP, CVBS: 960H

**iMAGE SETTING** Brightness, Sharpness, DNR, Mirror, Smart IR

BLC Support Support

D/N Mode Auto / Color / Black and White

White Balance Auto / Manual

**GENERAL** 

Operating Conditions -40 °F ~ 140 °F Humidity 90% or Less (Non-condensing)

Power Requirement 12 VDC / 24 VAC Power Consumption Max. 8.2W

 Dimensions
 Ø 5.35" × 4.01"

 Weight
 .99 lbs

 Warranty
 3 Years

Package ContentsCamera, Installation Manual/Template,

Installation Accessories





