



IPH2BL4L-21M-W

4MP OUTDOOR IR DAY/NIGHT
BULLET IP CAMERA



FEATURES

- 20FPS @ 4MP (2560 x 1440)
- 2.8-12mm Motorized Lens
- H.265 / H.264
- IR Range up to 100'
- DWDR, DNR, Day/Night
- Outdoor IP67
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	Micro SD/SDHC/SDXC Card (128GB), Local Storage and NAS (NFS,SMB/CIFS), ANR
Min. Illumination	0.01Lux @ F1.2, AGC ON, 0.018 @ F1.6 AGC On,	Alarm Trigger	Motion Detection, Video Tampering, Network Disconnected, IP Address Conflict, Illegal Login
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	2.8 to 12mm Motorized	General	One-key Reset, Dual-VCA, Anti-flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Day & Night	IR Cut Filter	API	ONVIF (Profile S, Profile G), ISAPI
IR Range	100'	Interface	1 RJ45 10M / 100M Self Adaptive Ethernet Port
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
3-axis Angle Adjustment	Pan: 0°~360°, Tilt: 0°~90°, Rotation: 0°~360°	Power Requirement	12VDC ± 20%, PoE (802.3af, Class 3)
COMPRESSION STANDARD		Power Consumption	12VDC Max. 11W PoE PoE (802.3at, 36V-57V), 0.4A-0.2A, Max. 12.9W
Video Compression	H.265 / H.264	Ingress Protection	IP67, TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
Type	Main Profile H.265 / H.264	Dimensions	Φ 4.1' x 9.6"
Video Bit Rate	32 Kbps ~ 8 Mbps	Weight	2.3 lbs
IMAGE		Warranty	3 Years
Max. Resolution	2560 x 1440	Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Main Stream	50Hz: 20fps (2560 x 1440), 25fps (2304 x 1296, 1920 x 1080, 1280 x 720), 60Hz: 20fps (2560 x 1440), 20fps (2304 x 1296, 1920 x 1080, 1280 x 720)		
Sub-stream	50Hz: 25fps (640 x 480, 640 x 360, 320 x 240), 60Hz: 30fps (640 x 480, 640 x 360, 320 x 240)		
Image Setting	Saturation, Brightness, Contrast, Sharpness, AGC, White Balance Adjustable by Client Software or Web Browser		
Day/Night Switch	Auto, Scheduled		

