

IPHBL8L-21M-W

8MP (4K) OUTDOOR IR WDR DAY/NIGHT
RUGGED BULLET IP CAMERA



FEATURES

- 15FPS @ 8MP (3840 x 2160)
- 2.8-12mm Motorized Lens
- H.265 / H.264
- IR Range up to 165'
- WDR, DNR, Day/Night
- Outdoor IP67, Vandalproof IK10
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.5" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC card (128GB) local storage, NAS (NFS, SMB, CIFS), ANR
Min. Illumination	Color: 0.01 Lux @ F1.2, AGC ON, 0 Lux with IR Color: 0.018 Lux @ F1.6, AGC ON, 0 Lux with IR	Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Illegal Login, HDD full, HDD error, Alarm Input, Alarm Output
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DNS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	2.8~12mm Motorized	General	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter, Three Streams
Day & Night	IR Cut Filter	Standard Interface	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
IR Range	165'	Audio Interface	1 RJ45 10M / 100M Self Adaptive Ethernet Interface 1 Input (3.5 mm), 1 Output (3.5 mm), Single Track
DNR	3D DNR	GENERAL	
WDR	120dB	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (Non-condensing)
3-axis Angle Adjustment	Pan: 0°~360°, Tilt: 0°~90°, Rotation: 0°~360°	Power Requirement	12 VDC ± 25%, Φ 5.5mm Coaxial Power Plug PoE (802.3at, class 4)
FOV	Horizontal: 105° to 34.5°, Vertical: 55° to 19° Diagonal: 125° to 40°	Power Consumption	12VDC: Max 17W, PoE: Max 19W
COMPRESSION STANDARD		Ingress Protection	IP67, IK10
Video Compression	H.265 / H.264	Dimensions	Φ5.67" x 13.10"
Type	Main Profile H.265 / H.264	Weight	4.17 lbs
Video Bit Rate	32 Kbps ~ 16 Mbps	Warranty	3 Years
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2 / PCM	Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-192Kbps(MP2L2)		
IMAGE			
Max. Resolution	3840 x 2160		
Frame Rate	50Hz: 12.5FPS @ 3840 x 2160, 20FPS @ 3072 x 1728 25FPS @ 2560 x 1920, 25FPS @ 2560 x 1440, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 15FPS @ 3840 x 2160, 20FPS @ 3072 x 1728 30FPS @ 2560 x 1920, 30FPS @ 2560 x 1440, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720		
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		
BLC	Support		
ROI Codec	Support, 1 Fixed Region for Each Stream		