



IPHMPTZ2-20X-IR

2MP OUTDOOR IR WDR DAY/NIGHT
PTZ IP CAMERA



FEATURES

- 30FPS @ 2MP (1920 x 1080)
- 4.7-94mm 20x Optical Zoom Lens
- H.264 / MJPEG
- IR Range up to 165'
- WDR, DNR, Day/Night
- Outdoor IP66
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.8" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC Card (64GB) Local Storage; Edge Recording
Min. Illumination	Color: 0.05 Lux @ f/1.6 AGC On B/W: 0.01 Lux @ f/1.6 AGC On, 0 Lux with IR	Alarm Trigger	Face Detection, Intrusion Detection, Line Crossing Detection, Region Entrance, Region Exiting, Audio Exception Detection, Motion Detection, Dynamic Analysis, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Shutter Speed	1/1s to 1/30,000s	Alarm Linkage	Alarm Actions, Such as Preset, Patrol Scan, Pattern Scan, Memory Card Video Record, Trigger Recording, Notify Surveillance Center, Upload to FTP / Memory Car / NAS, Send Email, etc.
Lens	4.7-94mm 20x Optical Zoom	Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Angle of View	58.3° to 3.2° (Wide to Tele)	Standard Interface	ONVIF, PSIA, CGI
Day & Night	IR Cut Filter		1 RJ45 10M/100M Ethernet Interface;
IR Range	165'		POE (802.3at, class4)
DNR	3D DNR	Audio Input	1 Channel
WDR	Support	Audio Output	1 Channel
Pan and Tilt	Pan: 360° Endless, Tilt: -5°~90°	GENERAL	
Speed	Zoom Speed: 2.7s (Optical Lens, Wide to Tele) Pan Speed: Configurable from 1°/s to 300°/s, Preset Speed: 250°/s, Tilt Speed: Configurable from 1°/s to 300°/s, Preset Speed: 200°/s	Operating Conditions	-22 °F ~ 149 °F, Humidity 90% or less
Number of Presets	300	Power Requirement	12VDC and PoE (802.3at, class4)
Patrols	8 Patrols, Up to 32 Presets Per Patrol	Power Consumption	Max. 18W, IR Light 5W Max.
COMPRESSION STANDARD		Ingress Protection	IP66 (Outdoor), TVS 4,000V Lightning Protection, Surge Protection and Voltage Transient Protection
Video Compression	H.264 / MJPEG	Dimensions	Φ6.67" x 6.34"
Triple Streams	Support	Weight	5.4 lbs
Audio Compression	G.711alaw / G.711ulaw / G.722.1 / G.726 / MP2L2 / PCM	Warranty	1 Year
IMAGE		Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories
Max. Resolution	1920 x 1080		
Frame Rate	Main Stream: 50Hz: 25FPS @ 1920 x 1080, 25FPS @ 1280 x 960, 25FPS @ 1280 x 720, 60Hz: 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720, 30FPS @ 1280 x 720		
BLC	Support		



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900