



4MP OUTDOOR IR WDR DAY/NIGHT BULLET IP CAMERA



- 30FPS @ 4MP (2688 x 1520)
- 4mm Fixed Lens
- H.265 / H.264
- IR Range up to 165'
- WDR, DNR, Day/Night
- Outdoor IP67
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

CAMERA			NETWORK		
Image Sensor	1/3" Progressive Scan CMOS		Network Storage	Micro SD/SDHC/SDXC Card (128G), Local Storage and NAS (NFS,SMB/CIFS), ANR	
Min. Illumination	0.01Lux @ F1.2, AGC ON, 0.018Lux @ F1.6, AGC ON, 0 Lux with IR		Alarm Trigger	Motion Detection, Video Tampering, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error	
Shutter Speed	1/3s to 1/100,000s		Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour	
Lens	4mm		General	One-key Reset, Anti-flicker, Three Streams, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter	
Day & Night	IR Cut Filter		Standard Interface	ONVIF (Profile S, Profile G), ISAPI 1 RJ45 10M/100M Self-Adaptive Ethernet Port	
IR Range	165'				
DNR	3D DNR				
WDR	120dB				
3-axis Angle Adjustment	Pan: 0°-360°, Tilt: 0°-100°, Rotate: 0°-360°				
COMPRESSION STANDARD					
Video Compression	H.265 / H.264 / MJPEG				
Type	Main Profile H.265/H.264				
Video Bit Rate	256 Kbps ~ 16 Mbps				
Three Streams	Supported				
IMAGE			GENERAL		
Max. Resolution	2688 x 1520		Operating Conditions	-22°F ~ 140°F	
Frame Rate	60Hz: 30FPS @ 2688x1520, 30FPS @ 2560x1440, 30FPS @ 2304x1296 30FPS @ 1920x1080 50Hz: 25FPS @ 2688x1520, 25FPS @ 2560x1440, 25FPS @ 2304x1296 25FPS @ 1920x1080		Power Requirement	Humidity 95% or Less (Non-condensing)	
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser		Power Consumption	12VDC ± 25%, PoE (802.3af)	
BLC	Support		Protection	Max. 7.5W IP67, TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection	
ACCESSORIES			Dimensions	15.2" x 6.1" x 6.1"	
Junction Box JB150	Junction Box JB200	Pole Mount POLEMT5	Weight	2.65 lbs	
			Warranty	3 Years	
			Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector	

