



IPH2BLX4-3-W

4MP OUTDOOR IR WDR DAY/NIGHT
BULLET IP CAMERA



FEATURES

- 30FPS @ 4MP (2688 x 1520)
- 2.8mm Fixed Lens
- H.265 / H.264
- IR Range up to 165'
- WDR, DNR, Day/Night
- Outdoor IP67
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/3" Progressive Scan CMOS	Network Storage	Micro SD/SDHC/SDXC Card (128G), Local Storage and NAS (NFS,SMB/CIFS), ANR
Min. Illumination	0.01Lux @ F1.2, AGC ON, 0.018Lux @ F1.6, AGC ON, 0 Lux with IR	Alarm Trigger	Motion Detection, Video Tampering, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Lens	2.8mm	General	One-key Reset, Anti-flicker, Three Streams, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Day & Night	IR Cut Filter	Standard Interface	ONVIF (Profile S, Profile G), ISAPI
IR Range	165'		1 RJ45 10M/100M Self-Adaptive Ethernet Port
DNR	3D DNR		
WDR	120dB		
3-axis Angle Adjustment	Pan: 0°-360°, Tilt: 0°-100°, Rotate: 0°-360°		
COMPRESSION STANDARD			
Video Compression	H.265 / H.264 / MJPEG		
Type	Main Profile H.265/H.264		
Video Bit Rate	256 Kbps ~ 16 Mbps		
Three Streams	Supported		
IMAGE		GENERAL	
Max. Resolution	2688 x 1520	Operating Conditions	-22°F ~ 140°F
Frame Rate	60Hz: 30FPS @ 2688x1520, 30FPS @ 2560x1440, 30FPS @ 2304x1296 30FPS @ 1920x1080 50Hz: 25FPS @ 2688x1520, 25FPS @ 2560x1440, 25FPS @ 2304x1296 25FPS @ 1920x1080	Power Requirement	Humidity 95% or Less (Non-condensing)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser	Power Consumption	12VDC ± 25%, PoE (802.3af)
BLC	Support	Protection	Max. 7.5W
		Dimensions	IP67, TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
		Weight	15.2" x 6.1" x 6.1"
		Warranty	2.65 lbs
		Package Contents	3 Years
			Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
ACCESSORIES			
Junction Box JB150	Junction Box JB200	Pole Mount POLEMT5	
			  



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900