



IPHPTZ2-25X-IR

2MP OUTDOOR IR WDR DAY/NIGHT
PTZ IP CAMERA



FEATURES

- 30FPS @ 2MP (1920 x 1080)
- 4.8-120mm 25x Optical Zoom Lens
- H.265 / H.264 / MPEG4 / MJPEG
- IR Range up to 330'
- WDR, DNR, Day/Night
- Outdoor IP66
- 12VDC / PoE+
- Includes Gigabit 30 Watt PoE Injector
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.8" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC Card (128GB) Local Storage; Edge Recording
Min. Illumination	Color: 0.005 Lux B/W: 0.001 Lux, 0 Lux with IR	Protocols	IPv4 / IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
Shutter Speed	1/1s to 1/30,000s	Interface	1 RJ45 10M/100M Ethernet interface
Lens	4.8-120mm 25x Optical Zoom	GENERAL	
Angle of View	Horizontal FOV: 57.6 ~ 2.5 degree (Wide-Tele), Vertical FOV: 34.4 ~ 1.4 (Wide-Tele) Diagonal FOV: 64.5 ~ 2.9 (Wide-Tele)	Operating Conditions	-22 °F ~ 149 °F, Humidity 90% or less
Day & Night	IR Cut Filter	Power Requirement	12VDC / PoE 802.3at Class 4
IR Range	330'	Power Consumption	Max. 18W
DNR	3D DNR	Ingress Protection	IP66 (Outdoor), TVS 4,000V Lightning Protection, Surge Protection and Voltage Transient Protection
WDR	Yes	Dimensions	Φ6.48" x 11.61"
Pan and Tilt	Pan: 360° Endless, Tilt: -15°~90° (Auto Flip)	Weight	4.41 lbs
Speed	Pan Manual Speed: 0.1° to 80°/s, Pan Preset Speed: 80°/s	Warranty	1 Year
COMPRESSION STANDARD		Package Contents	Camera, Gigabit 30 Watt PoE Injector, 1 1/2" Pipe Thread Adapter, Installation CD/Manual/Template, Installation Accessories
Video Compression	H.265 / H.264 / MPEG4 / MJPEG		
Dual Streams	Supported		
IMAGE			
Max. Resolution	1920 x 1080		
Frame Rate	Main Stream: 50Hz: 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720, 60Hz: 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720, 30FPS @ 1280 x 720 Sub Stream: 50Hz 25FPS @ 704 x 576, 25FPS @ 352 x 240, 60Hz: 30FPS @ 704 x 480, 30FPS @ 352 x 240, 30FPS @ 320 x 240		
BLC	Supported		
ROI Codec	Mainstream, Sub-stream and Third Stream Respectively Support Four Fixed Areas		
ACCESSORIES			
Wall Mount Bracket WM510	Ceiling Mount Adapter CLM100		
			



RainVision

www.rainvision.com ♦ 800 Shames Drive Westbury NY 11590 ♦ (516) 933-4900