



TVIPROID2-21M3-W

1080p INDOOR IR DAY/NIGHT DOME HD-TVI CAMERA
W/ 2.8-12MM MOTORIZED LENS



FEATURES

- 2MP (1920 x 1080) Resolution
- 2.8~12mm Motorized Lens
- HD-TVI Video Output
- IR Range Up to 100'
- WDR, DNR, Day/Night
- Indoor
- 12VDC / 24VAC
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		GENERAL	
Image Device	1/3" Progressive Scan CMOS	Working Temperature	-4°F ~ 113°F
Signal System	NTSC/PAL	Humidity	Humidity 90% or Less (non-condensing)
Effective Pixels	1920 (H) x 1080 (V)	Power Supply	12 VDC, 24 VAC
Min. Illumination	Color: 0.005 Lux @ (F1.8, AGC ON), 0 Lux with IR	Power Consumption	Max. 7W
Shutter Time	1/30s NTSC, 1/25s PAL to 1/50,000s	IR Range	Up to 100 ft
Lens	2.8-12mm Motorized Varifocal Lens	Communication	Up the Coax (Need UTC Controller), Protocol: Pelco-C(HD-TVI Output)
Angle of view	103° - 32.1°	Dimensions	Φ 5.35" x 4.02"
Lens Mount	φ14	Warranty	3 Years
Angle Adjustment	Pan: 0 - 340°, Tilt: 0 - 75°, Rotation: 0 - 355°	Weight	1.32 lb
Day & Night	IR with Cut Filter		
Synchronization	Internal synchronization		
WDR	120dB		
Video Frame Rate	30FPS @ 1080p NTSC, 25FPS @ 1080p PAL		
HD Video Output	1080p HD-TVI output		
MENU			
AGC	Support		
D/N Mode	Auto / Color / BW (Black and White)		
White Balance	ATW, Manual		
Privacy Mask	On/Off, 4 Programmable Privacy Masks		
Motion Detection	4 Programmable Motion Areas		
BLC	WDR/BLC/HLC/OFF		
Language	English, Chinese		
Functions	Brightness, Sharpness, Mirror, Smart IR		

