



IPH2CBW4-3-W

4MP INDOOR IR WDR DAY/NIGHT
CUBE IP CAMERA W/ BUILT-IN WIFI



FEATURES

- 30FPS @ 4MP (2688 x 1520)
- 2.8mm Lens
- H.265 / H.264 / MJPEG
- IR Range Up to 30'
- WDR, DNR, Day/Night, Built-in Mic and Speaker
- Indoor
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.9" Progressive Scan CMOS	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Min. Illumination	0.01 Lux @ F1.2 AGC On, 0.028 Lux @ F2.0 AGC On 0 Lux with IR	General	One-key Reset, Anti-Flicker, Three Streams, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter ONVIF (PROFILE S, PROFILE G), ISAPI
Shutter Speed	1/3s to 1/100,000s	Standard	
Lens	2.8mm @ F/1.6	INTERFACE	
Angle of View	Horizontal: 97°, Vertical: 67°, Diagonal: 121°	Audio	1 Built-in Mic, 1 Built-in Speaker, Mono Sound
Day & Night	IR Cut Filter	Communication	1 RJ45 10M/100M Self-adaptive Ethernet Port
IR Range	30'	On-board Storage	Built-in Micro SD/SDHC/SDXC Slot, Up to 128GB
DNR	3D DNR	SVC	Supports H.264 and H.265 Encoding
WDR	WDR	Reset Button	Yes
COMPRESSION STANDARD		WIFI	
Video Compression	H.265 / H.264 / MJPEG	Wireless Standards	IEEE 802.11b/g/n
Type	Main Profile H.265 / H.264	Frequency Range	2.412 GHz ~ 2.4835 GHz
Video Bitrate	256 Kbps ~ 16 Mbps	Channel Bandwidth	20/40 MHz
Audio Compression	G722.1 / G711ulaw / G711alaw / G726 / MP2L2 / PCM	Protocols	802.11b: DQPSK, DBPSK, CCK 802.11g/n: OFDM/64-QAM, 16-QAM, QPSK, BPSK
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-160Kbps (MP2L2)	Security	WPA, WPA2
Three Streams	Supported	Transfer Rates	11b: 11Mbps, 11g: 54Mbps, 11n: up to 150Mbps
IMAGE		GENERAL	
Max. Resolution	2688 x 1520	Operating Conditions	14 °F ~ 140 °F, Humidity 95% or Less Non-condensing
Frame Rate	50Hz: 25FPS @ 2688 x 1520, 25FPS @ 1920 x 1080, 60Hz: 30FPS @ 2688 x 1520, 30FPS @ 1920 x 1080	Power Requirement	12 VDC ± 25% , PoE (802.3af)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser	Power Consumption	Max. 7W
BLC	Supported	Dimensions	4.1" x 2.6" x 1.13"
ROI	Supported	Weight	.3 lbs
NETWORK		Warranty	3 Years
Network Storage	NAS (NFS, SMB/CIFS), ANR, Micro SD/SDHC/SDXC Card (128 GB)	Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories
Alarm Trigger	Motion Detection, Video Tampering, Network Disconnected, IP Address Conflict, HDD Full, HDD Error, PIR, Illegal Login		



RainVision

www.rainvision.com ♦ 1 Enterprise Place Hicksville NY 11801 ♦ (516) 933-4900