

TVIHD5ID-21M-W

5MP INDOOR IR DAY/NIGHT DOME HD-TVI CAMERA W/ 2.8-13.5MM MOTORIZED LENS



FEATURES

- 5MP (2592 x 1944) Resolution
- 2.8~13.5mm Motorized Lens
- HD-TVI / HD-CVI / AHD Video Output
- IR Range Up to 100'
- · WDR, DNR, Day/Night
- Indoor
- 12VDC / 24VAC
- Avaiable in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards. Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA 1/3" Progressive Scan CMOS **Image Device** Signal System NTSC/PAL

Effective Pixels 1920 (H) x 1080 (V)

Min. Illumination Color: 0.005 Lux @ (F1.8, AGC ON),

0 Lux with IR

Shutter Time 1/30s NTSC, 1/25s PAL to 1/50,000s 2.8-13.5mm Motorized Varifocal Lens Lens

Angle of view 103° - 32.1°

Lens Mount

Pan: 0 - 340°, Tilt: 0 - 75°, Rotation: 0 - 355° Angle Adjustment

Day & Night IR with Cut Filter Synchronization Internal synchronization

WDR 120dB

Video Frame Rate NTSC: 20FPS @ 5MP, 30FPS @ 4MP,

30FPS @ 1080p

PAL: 20FPS @ 5MP, 30FPS @ 4MP,

30FPS @ 1080p

MENU

White Balance

HD Video Output HD-TVI, HD-CVI, AHD Output

AGC Support

D/N Mode Auto / Color / BW (Black and White)

ATW, Manual

Privacy Mask On/Off, 4 Programmable Privacy Masks

4 Programmable Motion Areas

Motion Detection WDR/BLC/HLC/OFF BLC English, Chinese Language

Brightness, Sharpness, Mirror, Smart IR **Functions**

GENERAL

-4°F ~ 113°F Working Temperature

Humidity Humidity 90% or Less (non-condensing)

Power Supply 12 VDC, 24 VAC **Power Consumption** Max. 7W

IR Range Up to 100 ft Communication

Up the Coax (Need UTC Controller), Protocol: Pelco-C(HD-TVI Output)

Dimensions Φ 5.35" x 4.02"

3 Years Warranty 1.44 lb Weight





