



IPH2BL8L-3-W

8MP (4K) OUTDOOR IR WDR DAY/NIGHT
RUGGED BULLET IP CAMERA



FEATURES

- 20FPS @ 8MP (3840 x 2160)
- 2.8mm Fixed Lens
- H.265 / H.264
- IR Range up to 100'
- WDR, DNR, Day/Night
- Outdoor IP67, Vandal-proof IK08
- 12VDC, PoE
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.5" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC card (128GB) local storage, NAS (NFS,SMB/CIFS), ANR
Min. Illumination	0.01Lux @ F1.2, AGC ON, 0 Lux with IR	Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Illegal Login, HDD full, HDD error
Shutter Speed	1/3s to 1/100,000s	Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
Lens	2.8mm	General	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Lens Mount	M12	Standard Interface	ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI
Day & Night	IR cut filter with auto switch		1 RJ45 10M / 100M Self Adaptive Ethernet Interface
IR Range	100'		
DNR	3D DNR		
WDR	120dB		
3-axis Angle Adjustment	Pan: 0°~360°, Tilt: 0°~90°, Rotation: 0°~360°		
COMPRESSION STANDARD		GENERAL	
Video Compression	H.265 / H.264	Operating Conditions	-22 °F ~ 140 °F, Humidity 95% or less (non-condensing)
Type	Main Profile H.265 / H.264	Power Requirement	DC12V ± 25%, PoE (802.3af)
Video Bit Rate	32 Kbps ~ 16 Mbps	Power Consumption	Max. 7.5W
Triple streams	Support	Ingress Protection	IP67
IMAGE		Dimensions	Φ2.76" x 6.1"
Max. Resolution	3840 x 2160	Weight	.9 lbs
Frame Rate	60Hz: 20FPS @ 3840 x 2160, 30FPS @ 2560 x 1920, 30FPS @ 2560 x 1440, 30FPS @ 1920 x 1080, 30FPS @ 1280 x 720, 50Hz: 20FPS @ 3840 x 2160, 25FPS @ 2560 x 1920, 25FPS @ 2560 x 1440, 25FPS @ 1920 x 1080, 25FPS @ 1280 x 720	Warranty	3 Years
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness Adjustable by Client Software or Web Browser	Package Contents	Camera, Installation CD/Manual/Template, Mounting Screws, Weathertight Connector
BLC	Support		
ROI Codec	Support		
ACCESSORIES			
Junction Box JB125	Pole Mount POLEMT5		
			



RainVision

www.rainvision.com ♦ 800 Shames Drive, Westbury NY 11590 ♦ (516) 933-4900