TVIHD5VD-21MA-W

5MP STARLIGHT OUTDOOR IR DAY/NIGHT DOME HD-TVI CAMERA W/ 2.8-13.5MM AUTO-FOCUS MOTORIZED LENS

FEATURES

- 5MP (2592 x 1944) Resolution
- 2.7~13.5mm Auto-Focus Motorized Lens
- HD-TVI / HD-CVI / AHD Video Output
- IR Range Up to 195'
- Starlight, WDR, 3D DNR, Day/Night
- Outdoor IP67, Vandal-proof IK10
- 12VDC/24VAC
- Mounting screw holes line up to a single gang electrical box
- Available in White or Black

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA	
Image Sensor	5MP CMOS Image Sensor
Min. Illumination	Color: 0.003 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	NTSC: 1/30s to 1/50,000s PAL: 1/25s to 1/50,000s
Lens	2.7~13.5mm Auto-Focus Motorized Varifocal Lens
Day & Night	IR Cut Filter
IR Range	Up to 195'
DNR	3D DNR
WDR	Supported
3-axis Adjustment	Pan: 0°~355°, Tilt: 0°~75°, Rotate: 0°~355°
Horizontal Field of View	92.3°~29.3°
Synchronization	Internal Synchronization
Communication	Up the Coax, HD-TVI Output
IMAGE	
Max. Resolution	2560 x 1944
Frame Rate	NTSC: 20FPS @ 5MP, 30FPS @ 4MP, 30FPS @ 1080p, PAL: 20FPS @ 5MP, 25FPS @ 4MP, 25FPS @ 1080p
Image Settings	Brightness, Sharpness, 3D DNR, Mirror, Smart IR
BLC	Yes
AGC	Yes
D/N Mode	Auto / Color / Black and White
White Balance	Auto / Manual

GENERAL	
Operating Conditions	-40 °F ~ 140 °F Humidity 90% or Less (Non-condensing)
Power Requirement	12 VDC ±25%, 24 VAC ±25%
Power Consumption	Max. 8W
Ingress Protection	IP67, IK10
Dimensions	Ø 5.5" x 5.0"
Weight	1.41 lbs
Warranty	3 Years
Package Contents	Camera, Installation Manual/Template, Installation Accessories





Camera base has multiple screw holes so the camera can be mounted to standard size electrical boxes.