



TVIHD8BL-21MA-W

8MP OUTDOOR IR DAY/NIGHT
BULLET HD-TVI CAMERA



FEATURES

- 15FPS @ 8MP (3840 x 2160)
- 2.7~13.5mm Auto-focus Motorized Lens
- HD-TVI / HD-CVI / AHD / Analog Video Output
- IR Range up to 260'
- DWDR, DNR, Day/Night
- Outdoor IP67
- 12VDC / 24VAC
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA Image Sensor 8.29 MP CMOS Image Sensor Min. Illumination Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR Shutter Speed PAL: 1/12.5s to 1/50,000s NTSC: 1/15s to 1/50,000s Lens 2.7~13.5mm Auto-focus Motorized Varifocal Lens Day & Night IR Cut Filter IR Range 260' DNR Supported DWDR 105 dB 3-axis Adjustment Pan: 0°~360°, Tilt: 0°~90°, Rotate: 0°~360° Horizontal Field of View 108.1°~45.6° Synchronization Internal Synchronization Communication Up the Coax, HD-TVI Output		GENERAL Operating Conditions -40 °F ~ 140 °F Humidity 90% or Less (Non-condensing) Power Requirement 12 VDC ±25%, 24 VAC ±25% Power Consumption Max. 10.8W Ingress Protection IP67 Dimensions 10" x 3.62" x 3.33" Weight 1.53 lbs Warranty 3 Years Package Contents Camera, Installation Manual/Template, Installation Accessories	
IMAGE Max. Resolution 3840 x 2160 Frame Rate HD-TVI: 15FPS @ 8MP, 12.5FPS @ 8MP, 20FPS @ 5MP, 30FPS @ 4MP, 25FPS @ 4MP, 30FPS @ 2MP, 25FPS @ 2MP, HD-CVI: 15FPS @ 8MP, 12.5FPS @ 8MP, AHD: 20FPS @ 5MP, CVBS: 960H IMAGE SETTING BLC Brightness, Sharpness, DNR, Mirror, Smart IR Support AGC Support D/N Mode Auto / Color / Black and White White Balance Auto / Manual			
ACCESSORIES Junction Box JB150 		Pole Mount POLEMT5 	

