

IPHMPTZ4-25X-IR

4MP OUTDOOR IR WDR DAY/NIGHT
PTZ IP CAMERA



FEATURES

- Up to 30FPS @ 4MP (2560 x 1440)
- 4.8-120mm 25x Optical Zoom, 16x Digital Zoom Lens
- H.265+ / H.265 / H.264+ / H.264
- IR Range up to 150'
- Day/Night, DWDR, 3D DNR
- Outdoor IP66
- 12VDC/PoE+
- Available in White

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

CAMERA		NETWORK	
Image Sensor	1/2.8" Progressive Scan CMOS	Network Storage	micro SD/SDHC/SDXC Card (64GB) Local Storage; Edge Recording
Min. Illumination	Color: 0.005 Lux @ F1.6 AGC On B/W: 0.001 Lux @ F1.6 AGC On, 0 Lux with IR	Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Shutter Speed	1/1s to 1/30,000s	Simultaneous Live View	Up to 6 channels
Lens	4.8-120mm 25x Optical Zoom	Security Measure	User authentication (ID and PW), Host authentication (MAC address); IP address filtering
Angle of View	57.6° to 2.5° (Wide to Tele)	SYSTEM INTEGRATION	
Day & Night	IR Cut Filter	Alarm Input	2 ch Alarm Input
IR Range	150'	Alarm Output	2 ch Alarm Output
DNR	3D DNR	Audio Input	1 ch Audio Input
DWDR	Support	Audio Output	1 ch Audio Output
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples	Memory Card	Built-in memory card slot, supporting Micro SD/SDHC/SDXC, up to 128GB
Number of Presets	300	Client	Rainvision CMS
Patrols	8 Patrols, Up to 32 Presets Per Patrol	GENERAL	
Power-off Memory	Support	Operating Conditions	-22 °F ~ 149 °F, Humidity 95% or less
Park Action	Pattern Scan / Pan Scan / Tilt Scan / Frame Scan / Panorama Scan / Random Scan	Power Requirement	12VDC and PoE (802.3at, class4)
PTZ Position Display	Support	Power Consumption	Max. 18W
Scheduled Task	Preset / Patrol / Pattern / Pan Scan / Tilt Scan / Random Scan / Frame Scan / Panorama Scan / Dome reboot / Self-test action / Alarm output	Ingress Protection	IP66 (Outdoor), TVS 4,000V Lightning Protection, Surge Protection and Voltage Transient Protection
COMPRESSION STANDARD		Dimensions	Φ6.67" x 6.34"
Video Compression	H.265+ / H.265 / H.264+ / H.264	Weight	5.4 lbs
Triple Streams	Support	Warranty	1 Year
IMAGE		Package Contents	Camera, Installation CD/Manual/Template, Installation Accessories
Max. Resolution	2560 x 1440		
Frame Rate	Main Stream: 60Hz: 30FPS @ 2048 x 1536, 60FPS @ 1920 x 1080, 30FPS @ 1280 x 960, 30FPS @ 1280 x 720		
3D DNR	Support		
BLC	Support		
DWDR	Support		