




TDVRL4

1080P RESOLUTION 4 CHANNEL HD-TVI/AHD/ANALOG
+ 1 CHANNEL IP DVR W/ UP TO 8TB STORAGE



FEATURES

- 4 Channel
- 48FPS @ 1080p Resolution
- H.264+/H.264 dual-stream video compression
- Supports 1 SATA HDD up to 8TB Total, 2 USB 2.0
- HDMI/VGA Simultaneous Video Output
- iPhone/iPad/Android/Windows Phone Compatible

Rainvision is a leading brand of HD and IP network video surveillance cameras and recording equipment. By utilizing the latest technology in the industry, Rainvision video surveillance cameras provide all of the crisp, clear image quality in any security application or environment. With incorporating the latest ONVIF Profile S standards, Rainvision allows for easy integration and interoperability.

SPECIFICATIONS

VIDEO/AUDIO INPUT		GENERAL	
Video Compression	H.264+/H.264	Power supply	12 VDC
Video Inputs	4-Ch BNC interface (1.0Vp-p, 75) supporting coaxitron connection	Consumption (without HDD)	15 W
Supported HD-TVI input	1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz	Working temperature	14 °F to 131 °F
Supported AHD input	720p/25Hz, 720p/30Hz	Working humidity	10% to 90%
CVBS input	Support	Chassis Type	19" rack-mountable 1U chassis
IP video input	1-Ch Up to 2.0 MP resolution	Dimensions (W × D × H)	12.4 × 9.5 × 1.8 inch
VIDEO/AUDIO OUTPUT		Weight (without HDD)	4.4 lbs
CVBS output	Support	Package Contents	TDVRL4, IR Remote, USB Mouse, Power Adapter, Installation Manual & CD
HDMI/VGA output	1-Ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60Hz, 1024 × 768/60 Hz		
Encoding resolution	When 1080p Lite mode not enabled: 1080p(non-real-time) / 720p / VGA / WD1 /4CIF/CIF; When 1080p Lite mode enabled: 1080p lite / 720p lite/VGA/WD1/4CIF/CIF		
Frame rate	Main stream: 25fps(P) / 30fps(N), Sub-stream: WD1/4CIF@12fps / 2CIF (non-real-time); CIF/QVGA/QCIF (real time)		
Video bit rate	32 Kbps to 6 Mbps		
Audio output	1-ch, RCA (Linear, 1 K)		
Audio bit rate	64 Kbps		
Dual-stream	Support		
Stream type	Video, Video & Audio		
Synchronous playback	4-Ch		
NETWORK MANAGEMENT			
Remote connections	128		
Network protocols	TCP/IP, PPPoE, DHCP, RV-connect Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF		
HARD DISK			
SATA	1 SATA interface		
Capacity	Up to 8TB capacity		
EXTERNAL INTERFACE			
Two-way audio input	1-Ch, RCA (2.0 Vp-p, 1 K) (using the audio input)		
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface		
USB interface	2 × USB 2.0		
Serial interface	1; RS-485 serial interface, half-duplex		

